

**CVBS HDCVI™**

**HDTVI AHD**



### FEATURES

- 5 MP resolution with Sony CMOS sensor
- IR illumination up to 20 meters
- Black tempered glass to improve IR transfer
- 2.8 mm fixed lens
- Transmission distance up to 300 meters
- WB, AE, DNR, mirror mode
- OSD menu
- 4 in 1 output (DIP switch): CVBS @960H, CVI @4MP, TVI @5MP, AHD @5MP
- IP66
- 3AXIS: wall and ceiling installation

#### CAMERA

Image sensor	1/2,9 Sony® Exmor CMOS, 5 MP		
Effective pixels	2560(H) x 1920(V)		
Resolution	HDTVI	5MP (2560x1920) / 4MP (2560x1440) / 1080P (1920x1080)	
	AHD	5MP (2560x1920) / 4MP (2560x1440) / 1080P (1920x1080)	
	HDCVI	4MP (2560x1440) / 1080P (1920x1080)	
	Analog	960H (960x576)	
IR illumination	18 leds SMD: 20 meters		
Minimum illumination	0,01 lux F1,2 (AGC On) / 0 lux IR ON		
Video output	AHD, HDCVI, HDTVI, 1 BNC CVBS (DIP switch)		

#### LENS

Lens	2,8 mm
------	--------

#### FUNCTIONS

Day/night	Auto (ICR), Color, B/W
OSD menu	Supported
White balance	Supported
Auto exposure	Supported
Noise reduction	DNR
Mirror mode	Supported

#### ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC
Working temperature	-10°C ~ +55°C
RH	<85% HR
Transmission distance	Up to 300 meters (theoretical) via 75-5 coaxial cable
Protection	IP66

#### PHYSICAL FEATURES

Case	PVC & metal
Dimensions	100 x 70 mm