

16 CH IP NVR IP . H265/H264/MPEG4








## KEY FEATURES

- 16 CH IP NVR IP
- H.265/H.264/MPEG4
- 16 CH @ 1080P
- Display up to 12MP
- Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc
- Recording 160 Mbps
- VGA @ 1080P and HDMI @ 4K
- 2 way audio
- Alarm: 4 in / 1 out
- 2 HDD SATA

## FEATURES

- 16 CH IP NVR, H.265/H.264/MPEG4
- Dual O/S system
- Enabled POS function up to 4 POS
- 1 LPR channel supported (done by LPR camera function)
- VCA events supported generated by cameras (motion detection, tripwire, intrusion, etc.)
- 16 IP camera input
- Input bandwidth: 160 Mbps
- Output bandwidth: 256 Mbps
- VGA (1080P) and HDMI (4K, 2K) video output
- 2 way audio: 1 RCA in / 1 RCA out
- Display resolution: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
- Recording resolution: 12MP, 8MP, 6MP, 5MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF
- Live display up to: 12MP
- 16 channel synchronized playback
- Decoding capacity: 16 CH @ 1080P, 4 CH @ 4K/8MP
- Alarm channels: 4 in / 1 out
- Storage: 2x SATA up to 6TB (HDD not included)
- Network interface: Ethernet RJ45 (10/100/1000M) auto-adaptive
- Compatible with ONVIF
- ANR technology
- Intelligent search (for IP NEXTGEN cameras)
- VCA supported of IP cameras
- P2P cloud, DDNS DEMES, Push and channel zero
- Plug&Play with IP NEXTGEN cameras
- Connections: 1x USB 2.0, 1x USB 3.0
- 16 independent ports on rear panel (100Mbps) PoE+ 802.3af/at
- Power supply: 100V ~ 240V AC
- PoE consumption: ≤200W
- NVR consumption: ≤15W (without HDD and PoE)
- Working temperature: -10°C ~ +55°C
- RH: 10~90%
- Dimensions: 380 x 290 x 45 mm
- Weight: ≤3 kg