

## PCT-BNC-6

Universal BNC Compression Connector, Series 6 60% through Quad-Shield



<b>GENERAL SPECIFICATIONS</b>	
Bandwidth	5 MHz to 3 GHz
Impedance	75 Ohms (Nominal)
Return Loss	Minimum -30 dB to 1 GHz
Shielding Effectiveness	-80 dB Minimum
Insertion Loss	≤ .2dB @ 1GHz
Operating Voltage	90 V (at 60 Hz continuous AC)
Operating Temperature	-40° F to +140° F, -40° C to +60° C
Cable Range	RG6 Cable 60% through Quad-Shield
Cable Retention	>50 lb. (22.68 kg.) , Ambient Temperature
Cable Insertion	<15 lb. maximum insertion force, Ambient Temperature
<b>PHYSICAL CHARACTERISTICS</b>	
Length Before Compression	1.45 inches (36.99mm)
Length After Compression	1.28 inches (32.55mm)
Pin Diameter	.053 inches(1.37mm)
Mating Mechanism	75 ohm Bayonet Mounting BNC Male Connector
Construction Material	Nickel Plated Brass
Insulator	Delrin Insulator
Pin Construction	Beryllium Copper / Gold Plated Brass
<b>TOOLING</b>	
Compression tool	PCT-AIO-CT
<b>PART NUMBER</b>	
PCT-BNC-6	Universal BNC Compression Connector, Series 6 60% through Quad Shield