

FP2 GR CQR Przycisk wyjścia awaryjnego



- Typ przycisku - wciskany / resetowalny
- Wskaźnik zadziałania - LED
- Rezystor - 470 lub 680Ω
- Styk - 30VDC, 5A
- Klasa szczelności - IP44
- Obudowa - ABS
- Przycisk - poliwęglan
- Wymiary - 87x87x55mm
- Kolor - zielony



FP2 GR CQR to resetowalny przycisk wyjścia awaryjnego typu "Naciśnij mocno" - działa bez zbicia szybki. Przycisk wyjścia awaryjnego FP2 GR CQR jest umieszczony w obudowie z ABS w kolorze zielonym. Przycisk jest wykonany z poliwęglanu.

Dane techniczne

Typ przycisku	Wciskany - resetowalny
Wskaźnik zadziałania	Dioda LED
Rezystor	470 lub 680 W
Styk	30VDC, 5A
Klasa szczelności	IP44
Wykonanie	Obudowa - ABS, przycisk - poliwęglan
Wymiary	87x87x55mm
Kolor	Zielony

CQR Security		
<u>EC DECLARATION OF CONFORMITY</u>		
We: CQR Security of: 125 Pasture Road, Moreton, Wirral, Merseyside. CH46 4TH United Kingdom		
In accordance with the following Directive:- 2004/108/EC The Electromagnetic Compatibility Directive		
Hereby declare that:	Model No: FP2/* (*notes the colour e.g. RD= red)	
	Brand Name: CQR	
	Description: Manual Call Point.	
I, the undersigned, hereby declare that the equipment specified above is considered benign and therefore complies with all applicable Essential Requirements of the Directive.		
Name: Nigel van Woerdekom	Signed: 	
Position: Technical Manager		
On 6 th January 2012 Moreton Wirral		
CQR Security, 125 Pasture Road, Moreton, The Wirral. CH46 4TH Tel: +44(0)151 606 9595 Fax: +44(0)151 606 1122 e-mail: info@cqr.co.uk CQR Security: A division of OSL Group Ltd, Registered office: Imperial Works, Sheffield Road, S9 2YL Registered in England No. 4333830		